

MAXI BUF

A pilot plant designed for process development, membranes scale up testing, quality assurance and small-scale/production range within microfiltration or ultrafiltration phase.

A simple self-contained unit with a hold-up volume (circa 120 Liters), Lowara feed and recirculation pumps with VSD, 3 membrane modules, heat exchanger, pressure & temperature sensors, flowmeters and a control panel. All mounted on a welded AISI 304 stainless-steel framework.



Application Range

Microfiltration (MF)	Ultrafiltration (UF)
up to 30 L/min	up to 30 L/min

Electrical Power Supply	Connections
400 Volts	Inlet to feed pump: 1 1/2" hose tail
3-phase (5 pins)	HE in/out cooling water: 1/2" OD hose
50 Hz. 40 Amp	Permeate outlet: 3/4" OD hose tail
Motor rating: 7.5 KW (feed pump @ 3 KW, recirculation pump @ 4 KW)	Shroud outlet: 1/2" ABS pipe
	Concentrate outlet UF: 1" OD hose tail

Size & Weight

Dimension			Unit & Package	Unit Only
Length	Height	Width		
4.2 m	1.4 m	0.8 m	450 kg	360 kg

Framework

Welded stainless-steel frame fabricated from a high-grade 304 SS for corrosion resistance, high rigidity and temperature resistance.

Module

3 x 12 ft (3.6 m) B1 Module

Comprised of 18 perforated stainless-steel tubes in the form of a shell & tube, each tube fitted with a membrane element. The modules are designed with a twin entry end caps; providing 2 parallel channels, each of 9 tubes in series. This allows viscous materials to be processed and high cross flow velocities to be used with acceptable pressure drop.

2020 11 11 DS

Specification per module

- Membrane area: 2.6 m²
- Module weight: 33.7 kg
- Hold-up volume: Tube-side 8.4 L
Shroud-side 20 L
- Membrane tube ID: 12.7 mm.
- Total membrane area modules: 7.8 m²

Plant mechanical operating limit

- Max operating pressure: up to 10 bar
- Max pressure drop: 5 bar per module
- Max operating temperature: up to 70°C

Heat Exchanger (HE)

Shell & tube type heat exchanger 4 ft (1.2 m)

Process fluid is piped from the outlet of the recirculation pump through all 18 tubes in series within the heat exchanger while cooling water passes at low pressure (1-3 bar) through the shroud (shell) side. Cooling media flow could be up to 20 L/min.

Corporate Office

PCI Membranes
Unit 11, Fulcrum 2, Solent Way, Whiteley, Fareham,
Hampshire, PO15 7FN, United Kingdom

Phone

Phone: + 44 1489 563 470

Email: pcimembranes@filtrationgroup.com

Online


Website: www.pcimembranes.com

www.filtrationgroup.com

MAXI BUF

A pilot plant designed for process development, membranes scale up testing, quality assurance and small-scale/production range within microfiltration or ultrafiltration phase.

A simple self-contained unit with a hold-up volume (circa 120 Liters), Lowara feed and recirculation pumps with VSD, 3 membrane modules, heat exchanger, pressure & temperature sensors, flowmeters and a control panel. All mounted on a welded AISI 304 stainless-steel framework.



Pumps, IEC Motors & VSD

- Feed Pump: Lowara centrifugal pump, model 5SVH18V030T fitted with Hydrovar HV4.040 VSD controller. 3 m³/hr max flow, 3 KW motor, 10 bar max pressure.
- Recirculation Pump: Lowara centrifugal pump, model 10SVH09V040T fitted with Hydrovar HV4.040 VSD controller. 9 m³/hr max flow, 4 KW motor, 10 bar max pressure.
- Flows from both pumps can be adjusted via the HMI screen.

Flowmeter

- 3 Endress + Hauser electromagnetic flowmeters are installed on the unit: One on the feed line (Promag 10P25, DN25 1"). Two other flowmeters are installed on the retentate line and recirculation line (Promag 10P50, DN50 2").
- An IFM flowmeter is also installed on the permeate line.

Pressure & Temperature Sensor.

Pressure Control Valve

- Pump outlet pressure, modules inlet and outlet pressure are constantly monitor via independent Endress + Hauser PMC131 pressure transmitter and display on the HMI screen.
- Outlet temperature from all modules is monitor via Endress + Hauser TR11 thermometer sensor and display on the HMI screen.

Pressure Control Valve

- Two hand operated diaphragm valves are installed on the retentate line to create the back pressure and control flow.

Safety

- The unit is designed to the principles of Supply of Machinery (Safety) Regulations 1992 and are safe if operated in accordance with the procedures in the operating manual.

Corporate Office

PCI Membranes
Unit 11, Fulcrum 2, Solent Way, Whiteley, Fareham,
Hampshire, PO15 7FN, United Kingdom

Phone

Phone: + 44 1489 563 470

Email: pcimembranes@filtrationgroup.com

Online

Website: www.pcimembranes.com

www.filtrationgroup.com